

Declaration of Conformity according to EN 13141-7:2004 / EN308

Technical Sciences

Laan van Westenenk 501 7334 DT Apeldoorn Postbus 342 7300 AH Apeldoorn

www.tno.nl

T +31 88 866 22 12 F +31 88 866 22 48 infodesk@tno.nl

TNO-060-DTM-2013-01161

Determination of the energetic efficiency of the energy recovery appliance "Renovent Excellent 400"
Test report in accordance with EN 13141-7:2004 / EN308

Date May 2013

Author(s) H.A.J. Hammink

Sponsor Brink Climate Systems BV

R.D. Bügelstraat 3 7951 DA Staphorst

Project number 060.01122

Keywords heat recovery

efficiency

All rights reserved.

No part of this publication may be reproduced and/or published by print, photoprint, microfilm or any other means without the previous written consent of TNO.

In case this report was drafted on instructions, the rights and obligations of contracting parties are subject to either the General Terms and Conditions for commissions to TNO, or the relevant agreement concluded between the contracting parties. Submitting the report for inspection to parties who have a direct interest is permitted.

© 2013 TNO



TNO-Results

Determination of the energetic efficiency of the energy recovery appliance "Renovent Excellent 400", Test report in accordance with EN 13141-7 / EN308

Declaration of Conformity | TNO-060-DTM-2013-01161

2/2

Declaration of Conformity according to EN 13141-7:2004 / EN308

On behalf of Brink Climate Systems B.V., located in Staphorst, the Netherlands, the determination of the energetic efficiency was carried out by TNO Technical Sciences in Apeldoorn, the Netherlands.

Testing was performed according to:

- EN13141-7:2004 Performance testing of mechanical supply- and exhaust air ventilation units for single-family dwellings
- EN308, heat exchangers Test procedures for establishing performance of air to air and flue gases heat recovery devices.

Key data for the tested unit:

Manufacturer: Brink Climate Systems B.V.

Type Renovent Excellent 400

Serial number: 420020104601

Year of construction: 2010
CE approval: Yes
Max. air flow 400 m³/h

Results for the energetic efficiency:

Air flow	Corrected	Power	Voltage	Current	Power factor
[m³/h]	η _{temp}	[W]	[V]	[A]	[-]
50	93.3	9.4	229.8	0.12	0.34
225	85.2	48.7	229.8	0.42	0.51
400	81.4	153.6	229.8	1.22	0.55

Date : 1 May 2013 Place : Apeldoorn

Signed:

Drs. P.M. van Hoorik

Research Manager Energy and Comfort Systems

Measurement results, leak tightness classification, fan characteristics and the functioning of the energy recovery appliance at low temperatures are given in short report BRR 060-APD-2011-00068, July 2011.